

Model : 3D2015

'Vari-speed'
Electric Label Dispenser

Designed & Manufactured
in the UK

Incorporates
Photocell
technology

*Increase the efficiency of hand-applying
self-adhesive labels*



Model : 3D2015

Semi -Automatic Label Dispenser

Specification

Power supply: 240Vac 50/60Hz or 110Vac 50/60Hz

Reel Width	155mm (6")
Reel Diameter	305mm (12")
Reel Weight	5.0kg
Reel Speed	35m/min max (variable)
Label Detection	Photocell or Microswitch (budget)
Label Source	Reel or Fanfold
Unit Weight	6.5Kg
Physical Dimensions	340, 250, 220mm (L, W, H)

The **Vari-Speed 3D2015 Label Dispenser** provides a fast and efficient way of manually applying self-adhesive labels. Robust steel chassis, quick and simple to set-up and operate. Each label is individually presented to the operator with the backing paper automatically removed and rewound.

- ◆ Designed and Manufactured in the U.K.
- ◆ Labels detected by a reflective modulated-light Photocell which can be used in all lighting conditions and does not impede label removal
- ◆ Variable Dispensing Speed (ensures the unit is compatible with virtually all label sizes and types)
- ◆ Holds reel diameters up to 305mm (12") and widths of 160mm (6")
- ◆ Presents operator with new label each time current one is removed.
- ◆ Removes and Rewinds backing paper
- ◆ Works with labels on Roll or Fanfold formats.
- ◆ Suitable for transparent labels
- ◆ Electronic braking system for precise label dispensing
- ◆ Simple to set-up and operate
- ◆ Robust coated-steel chassis design - Ideal for Workshop & Office Environments
- ◆ Available in 240Vac or 110Vac 50/60Hz versions
- ◆ Carrying Handle - for ease of transportation
- ◆ Can dispense labels as small as 5x 5mm
- ◆ Maintenance free
- ◆ Upgradeable

To Order, please quote the following model numbers:

3D2015B Label Dispenser with PHOTOCCELL Label sensor

3D2015A Label Dispenser with MICROSWI TCH Label sensor